



# Duracoat Self Priming Acrylic Roof Paint

## Features

- Contains non toxic anti corrosive pigments
- 100% Acrylic emulsion formulation
- UV resistant pigments, colours remain true for a long time
- Excellent obliteration
- Long lasting protection of roofs
- Excellent adhesion (no peeling), highly durable and weather resistant
- Repels water and will not soften and peel off
- Easy cleaning, no solvent smell, user and environment friendly
- Beautiful, smooth appearance

## Recommended for

Weather resistant coating for Galvanized roof, Granular tiles, Fibre-cement tiles, Clay Tiles


## General Description

Duracoat Self Priming Acrylic Roof Paint is an extremely durable, weather resistance and fully flexible coating for roofs. The tough formulation is resistant to UV light and offers superior water resistance. Advanced pigments and light stabilisers ensure that the wide range of colours remain true.

## Limitations

Do not apply when the surface temperature is below 10°C and above 45°C.

## Product Information

<b>Colour Range :</b> Deep Blue, Cornflower, Roof paint Red, Roof paint Green	<b>Technical Data</b>	
	Finish	Low sheen
	Spread Rate	10-12 m <sup>2</sup> /l when applied on a smooth, non porous surface
<b>Special Colors :</b> Special colors can be made available on request	Drying time	
	- Surface dry	20-30 mins
<b>Pack sizes :</b> 4 ltrs, 20 ltrs	- Recoating time	4 hours
	Application	By Brush, Rollers, Conventional Spray
<b>Technical Assistance:</b> If in doubt please contact our Technical department on 6823555/954	Thinning	DO NOT THIN. Paint is ready for use.
		Cleaning
Volatile Organic Compounds (VOC)		< 50 gm/l

---

## Duracoat Self Priming Acrylic Roof Paint

---

### Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material.

**Galvanised roof:** Clean new surfaces with Duracoat White spirit thoroughly. Ensure that the surface is completely clean and dry. Apply one coat of Duracoat Etching solution. Rust if any, should be sanded to bright metal. Then apply two coats of undiluted Duracoat Self Priming Acrylic Roof Paint. For previously painted surface, loose paint, chalk and dirt should be removed by scrapping, sanding and cleaning with water before applying Duracoat Self Priming Acrylic Roof Paint.

**Granular tiles, asbestos fibre-cement tiles, Clay tiles:** For new and previously painted surface in good condition, remove dust, dirt, loose granules, friable and powdery material by scrubbing with hard bristle brush and water. Allow surface to dry. Then apply two coats of undiluted Duracoat Self Priming Acrylic Roof Paint. Previously painted surface in poor condition should be stripped out completely.

### Precautions

- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

### Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

### Note

- When over coating a dark shade with a light shade three coats may be required

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to MSDS for additional health and safety information**

### Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information