



Duracoat Ultima Play Luxurio

Features

- Luxury metallic effect
- Special Luminous effect
- Customizable design
- Perfect for creating classic and modern Atmospheres
- Easy to apply

General Description

Ultima Play Luxurio is an interior decorative finish that has the ability to create prestigious surfaces, adorned with a delightful metallic fine effect. This effect adds to the appeal of modern-designed spaces, fostering a pleasant atmosphere.


Recommended for

New and old interior plasters, interior concrete walls, interior gypsum walls

Limitations

Do not apply when the temperature is below 10°C and above 40°C

Product Information

Colour Range : Available in a wide range of colors from Ultima Play Luxurio shade card	Technical Data	
	Finish	Metallic
Special Colors : Special colors can be made available on request	Spread Rate	4-6 Sq. Mt./Ltr when applied on a smooth surface.
	Drying time - Surface dry	45 mins
Pack sizes : 1ltr and 4 ltrs	Application	By Brush
Technical Assistance: If in doubt please contact our Technical department on 82355/954	Thinning	DO NOT THIN. Product is ready for use.
 <p>This product is environmentally friendly and has low VOC (volatile organic compounds)</p>	Cleaning	Clean all equipments with water.
	Volatile Organic Compounds (VOC)	< 50 gms/ltr

Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. Cracks and defects should be filled with appropriate crack filler followed by appropriate primer.

<p>New Unpainted surfaces: Cement plaster, Gypsum plaster : Apply one coat of Duracoat Vinyl Matt Deluxe or Duracoat Emulsion Undercoat as a primer.</p> <p>Apply one coat of Ultima Play Luxurio over the dry primer with the brush spreading the paint unevenly.</p>	<p>Previously painted surface : Remove loose and flaking paint back to sound substrate by scrapping and sanding. Sand glossy enamel surfaces thoroughly to an even matt finish, dust off. Follow the procedure as for new unpainted surfaces.</p>
--	--

Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Always pre test on a small area first

KEEP OUT OF REACH OF CHILDREN

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information